


# **Telescope Development for Space-based Gravitational Wave Observatories**

**Jeff Livas**

**NASA Goddard Space Flight Center**

**September 2015**

# Telescopes for Space-Based Gravitational-Wave Observatories: High-level Summary



## Objectives and Key Challenges:

- Establish a complete telescope design meeting optical, mechanical, thermal, and manufacturability requirements for possible US contribution to the eLISA L3 mission
- Fabricate and test a prototype
- Validate stray-light model
- Verify dimensional stability

## Significance of Work:

- First demonstration of a validated scattered-light model, and combined with previous demonstration of dimensional stability, provides a firm basis for realistic engineering-model design for a flight-qualifiable off-axis telescope.

## Approach:

- Use SGO-Mid and the ESA eLISA concepts as a reference
- Generate requirements per the ESA/SRE “Yellow Book”
- Use outside vendor design study results
  - (off-axis SiC recommended)
- Fabricate a prototype from the design
- Validate stray light model
- Need another iteration to demonstrate stability


## Key Collaborators:

- NASA Goddard optics branch
- Mechanical contractor Justin Ward
- Postdoc Shannon Sankar and Prof. Guido Mueller

## Current Funded Period of Performance:

- Oct 2012 – Sep 2015 NASA HQ SAT grant: scattered light
- Oct 2015 – Sep 2017 follow-on SAT grant: dimensional stability

Off-axis Prototype Model  
Afocal modified Cassegrain



## Recent Accomplishments:

- ✓ Signed prototype model contract
- ✓ Prototype CDR
- ✓ Prototype telescope delivered to GSFC
- ✓ Aligned prototype telescope at GSFC


## Next Milestone:

- Validate system-level scattered-light model (Sep 2015)

## Applications:

- Flagship gravitational-wave missions (eLISA)
- Laser ranging; precision metrology applications
- Laser communications


# Scattered Light Analysis



Mirror	RMS surface roughness (Å)	MIL-STD 1246D CL
M1	15	300
M2	15	200
M3	5	200
M4	5	200

Conflicting  
accounts of on-  
orbit levels

## Pupil Plane Scatter Irradiance




- Source power = 1W
- Total power on the detector =  $6.6 \times 10^{-11}$  W  $\rightarrow$  (barely) meets specification of less than  $10^{-10}$

mirror	Path#	# Rays	Power %	Power	1st scatter surface
3	7	2291695	74.947	4.9421e-11	.20140417_elisa_baseline.M3.Front
4	3	2711030	23.053	1.5201e-11	.20140417_elisa_baseline.M4.Front
2	11	2565386	1.9733	1.3012e-12	.20140417_elisa_baseline.M2.Front
1	14	1399213	0.026184	1.7266e-14	.20140417_elisa_baseline.M1.Front
Totals		8967324	100	6.5941e-11	

**M3 and M4 contribute most of the scattered light on the detector**


# Optical Test Setup: Current Status

## Optical Layout



- Telescope to be tested double-pass from the small aperture side
- Currently aligned to better than  $\lambda/30$
- Room temperature operation only
- Seems to be stable under normal lab conditions

## As installed in cleanroom



- Currently installing 1064 nm laser and test equipment
- Verify the same alignment at 1064 nm as with 633 nm interferometer
- Next step is to start measuring scattering